## VEHICLE **INSPECTION**

## Standard Imprint Header Standard Imprint City & Phone

MULTI-POINT INSPECTION										
N.	Date:RO/Tag#:				LL	OK FILL		OK FILL		
≥	Name:	Phone#: ()	FLUIDS	0	Engine Oil	O Power S	Steering	☐ Transmis		
						0 0		0 0	d with dipstick)	
ğ					Brake Reservoir	Window	v Washer	Coolant R	Recovery Reservoir	
Z	VIN#:				l Bassan	Datton: State of Licalth		Date and Can distant		
뛜	Year/Make/Model:Plate#:			Serviced	Batter,	y State of Health		Battery Con	_	
é	Odometer: Inspect Month:				0%					
S			<u>o</u>		Factory spec cold cranking amps Actual cold cranking amps					
O	Rewards#:Service Plan: YES \( \) NO \( \text{Member? YES} \( \) NO \( \text{Member? YES} \( \) NO \( \text{Member? YES} \( \text{NO} \)			0	Cooling	g System - Hoses and	d Piping			
EXTERIOR BODY	May contribute to vehicle efficiency and promote a greener environment  Check and OK at this time May require future attention Requires immediate attention		UNDER	0	O O Engine	Air Filter				
			tion 5	0	Engine Drive Belt(s)					
				0	Cabin Air Filter					
		8	Serviced	DUE		Serviced	DUE			
			ENANC	0	○THE WORKS		0	Engine Air Filter		
	Note any exterior body damage or defects on diagram  Serviced Serviced Serviced						0			
					Oil Change			○ Engine Coolant		
					Tire Rotation	n		Transmission Flu	id &/or Filter	
				0	Multi-Point	Inspection	0	Cabin Air Filter	N/A	
<u>.</u> ۾				0	Fuel Filter	N/A	0	Spark Plugs		
HORN	0	Horn Front Wipers Rear Wipers (If equ			K	Scheduled Maintenar	nce			
둕쭕	0	Windshield Front Lighting Headlights, Parking Lights, Turn Signals, Fog Lights, 4-Way Flasher								
≘ّھ	0	Rear Lighting - 4-Way Flasher, Taillights, Stop Lights, Plate Lights	This is only a partial list maintenance items and is NOT all-inclusive. Please consult your Owner's Manual for vehicle specific maintenance requirements.							
	Serviced	Brake Lining Over 5mm or 7/32* (Disc) or Over 2mm or 3/32" (Drum) 4mm to 5m	m or 4/32" to 7/3	2° (Disc) or I	1.01 to 2mm or 2/32" to 3.	/32* (Drum) 3mr	n or Less or 4/	'32" (Disc) or 1mm or 2/32"		
BRAKES		Left Front Brake Pad Thickness:	Roto	r Actual:	ual: R		Rotor Minimum Spec:		<u> </u>	
¥		Right Front Brake Pad Thickness:	Roto	Rotor Actual:		Rote	Rotor Minimum Spec:		○ 🖁	
뚪	0	Left Rear Brake     Pad/ Shoe Thickness:	Roto	r/Drum Act	tual: Rotor/Drun			Minimum Spec:		
	0	Right Rear Brake     Pad/Shoe Thickness:	Roto	r/Drum Act	tual:	Rote	Rotor Minimum Spec:  Rotor/Drum Minimum Spec:  Rotor/Drum Minimum Spec:			
								•		
UNDERCARRIAGE		Ceft Front suspension, struts, steering linkage, brake lines/hoses Notes:								
		Right Front suspension, struts, steering linkage, brake lines/hoses Notes:								
	0	● ○ ● Left Rear suspension, shocks/struts, linkage, brake lines, hoses Notes:								
ζ,	0	Right Rear suspension, shocks/struts, linkage, brake lines, hoses Notes:								
出	0	Carbon Notes:								
3		O Drivetrain Notes:								
		Drivetrain Notes:								
	Serviced	Tire Tread Lining 7/32" or Greater / Over 5mm	6/32	to 4/32" / 5	5mm to 3mm		3/:	32" or Less / Less than 3mn	n	
	0	● ○ ● Left Front Tire Condition: Size:			Tread Depti	h: Age	:	* Tire PSI	:	
	0	Right Front Tire Condition: Size:		Tread Depth:		h: Age	:	* Tire PSI:		
SE	0	Left Rear Tire Condition:     Size:			Tread Depth:		Age: * Tire PSI:			
TIRES										
	0	Right Rear Tire Condition: Size:			Tread Depti		Ψ			
		Spare Tire Condition: Size:		Tread Depth:			:	* Tire PSI:	:	
		Spare Not Inspected: Ono Spare Tire Other/Comments:								
									placed after 6 years.	
		DESCRIPTION					PARTS	LABOR	TOTALESTIMATE	
Ot	ner Sei	rvices:								
lm	Immediate Services:									
Maintenance Needs										
						TOTAL				
Service Advisor: Customer Signature:										
Technician:										